



LED SURFACE-MOUNTED WALLWASHER DOWNLIGHT for INGRESS PROTECTION with LENS

Round, Ø 180mm | Tilting angle 0 - 25°






Light source	: High performance Philips Fortimo LED light module
Lumen output	: 1100lm; 2000lm
Light colour	: Warm white, 3000K; Natural white, 4000K
Power consumption	: 10 - 19W
System efficacy	: 79 - 100lm/W
CRI	: > 90
Voltage	: 220-240V / 50/60Hz (other voltages upon request)
Lifetime	: 50,000 hours (L70 at Tc 75°C)
Driver unit	: Philips Xitanium LED driver
	Operating temperature from -20 to +65°C
Housing	: Extruded aluminium with grey aluminium powder coating (RAL 9007). Other colours upon request.
Cover	: Die-cast aluminium with grey aluminium powder coating (RAL 9007) and clear tempered glass
Reflector	: High specular aluminium silver
Diffuser	: Wide angle frosted glass lens
Heat sink	: Die-cast aluminium alloy with high heat conductance
Cable	: 400mm length multi-core cable
Tilting angle	: 0 to 25° (lockable) with 350° rotation
DALI control	: Optional
Ingress protection	: IP 65
Optimum working temperature	: 25°C
Weight	: 5.26 kg

- 31011.103 (1100lm, 3000K)
- 31011.203 (2000lm, 3000K)
- 31011.104 (1100lm, 4000K)
- 31011.204 (2000lm, 4000K)

LED SURFACE-MOUNTED WALLWASHER DOWNLIGHT for INGRESS PROTECTION with LENS

Round, Ø 207mm | Tilting angle 0 - 25°



Light source	: High performance Philips Fortimo LED light module
Lumen output	: 2000lm
Light colour	: Warm white, 3000K; Natural white, 4000K
Power consumption	: 19 - 32W
System efficacy	: 77 - 100lm/W
CRI	: >95
Voltage	: 220-240V / 50/60Hz (other voltages upon request)
Lifetime	: 50,000 hours (L70 at Tc 75°C)
Driver unit	: Philips Xitanium LED driver
	Operating temperature from -20 to +65°C
Housing	: Extruded aluminium with grey aluminium powder coating (RAL 9007). Other colours upon request.
Cover	: Die-cast aluminium with grey aluminium powder coating (RAL 9007) and clear tempered glass
Reflector	: High specular aluminium silver
Diffuser	: Wide angle frosted glass lens
Heat sink	: Die-cast aluminium alloy with high heat conductance
Cable	: 400mm length multi-core cable
Tilting angle	: 0 to 25° (lockable) with 350° rotation
DALI control	: Optional
Ingress protection	: IP 65
Optimum working temperature	: 25°C
Weight	: 6.23 kg

- 31013.203 (2000lm, 3000K)
- 31013.203 (2000lm, 3000K)
- 31013.204 (2000lm, 4000K)
- 31013.204 (2000lm, 4000K)